





## DISC DIFFUSER



# REHAU

**REHAU's Fine Bubble** aerator systems represent the finest in German engineering and production technology. Each product is designed, manufactured, and tested to REHAU's superior standards of quality and certified to ISO9001 quality and ISO14001 (environmental) standards.

Pipe and disc aerators with the Patented 'Saddle Lock' connection system suitable for all major air distribution pipe dimensions





**RAUBIOXON PLUS (Silicone)** 



High temperature resistance of up to 120°C



High tear strength of 45 N/mm (acc. to ASTM D624B)



**RAUBIOFLEX (EPDM)** 



High temperature resistance of up to 80°C



High tear strength of 18 N/mm (acc. to DIN 53507A)

Article No.	Membrane ID (mm)	Air Distribution Pipe OD (mm)	Effective Length (mm)	Air Flow Range (Nm³/h)	*Max Airflov (Nm³/h)		
RAUBIOXON DUO PIPE AERATORS WITH SADDLE LOCK CONNECTION							
403786-600	Ø64	Ø88.9	1000	2 - 12	24		
401487-600	Ø64	Ø88.9	1500	3 - 18	36		
414185-600	Ø64	Ø88.9	2000	4 - 24	48		
417225-600	Ø64	Ø90	1000	2 - 12	24		
401503-600	Ø64	Ø90	1500	3 - 18	36		
413462-600	Ø64	Ø90	2000	4 - 24	48		
401508-600	Ø64	Ø110	1000	2 - 12	24		
401524-600	Ø64	Ø110	1500	3 - 18	36		
413522-600	Ø64	Ø110	2000	4 - 24	48		
401547-600	Ø64	Ø114.3	1000	2 - 12	24		
417203-600	Ø64	Ø114.3	1500	3 - 18	36		
417203-600	Ø64	Ø114.3	2000	4 - 24	48		
401645-600	Ø92	Ø110	1000	3 - 19	38		
401646-600	Ø92	Ø110	1500	4.5 - 28.5	57		
417205-600	Ø92	Ø110	2000	6 - 38	76		
400618-600	Ø92	Ø114.3	1000	3 - 19	38		
417197-600	Ø92	Ø114.3	1500	4.5 - 28.5	57		
417198-600	Ø92	Ø114.3	2000	6 - 38	76		
406048-600	**Ø92-L	Ø114.3	2000	6 - 38	76		
404716-600	**Ø92-L	Ø168.3	2000	6 - 38	76		
404721-600	**Ø92-L	Ø219.1	2000	6 - 38	76		
RAUBIOXON STD PIPE AERATORS WITH THREADED ROD CONNECTION							
208754-600	Ø64	Ø90, Ø110, Ø140, Ø160	500	1-6	12		
208755-600	Ø64	Ø90, Ø110, Ø140, Ø160	750	1.5 - 9	18		
208759-600	Ø64	Ø90, Ø110, Ø140, Ø160	1000	2 - 12	24		

RAUBIOXON STD PIPE AERATORS WITH 1¼" THREAD

500

750

1000

1-6

1.5 - 9

2 - 12

12

18

24

Ø88.9, Ø90, Ø110, Ø114.3

Ø88.9, Ø90, Ø110, Ø114.3

Ø88.9, Ø90,Ø110, Ø114.3

215676-600

209549-600

402364-600

Ø64

Ø64

Ø64



Article No.	Diameter (mm)	Air Distribution Pipe OD (mm)	Wall Thickness (mm)	Air Flow Range (Nm³/h)	*Max Airflow (Nm³/h)
		RAUBIOXON DISC AERATORS	:		
411335-600	DN200	Ø88.9, Ø90, Ø110, Ø114.3	-	0.5 - 5	10
415215-600	DN225	Ø88.9, Ø90, Ø110, Ø114.3	-	1-7	14
411345-600	DN300	Ø88.9, Ø90, Ø110, Ø114.3	-	1.5 - 11	22

#### DISC SADDLE



417081-006	DN200, DN225, DN300	Ø88.9	-	-	-
417003-006	DN200, DN225, DN300	Ø90	-	-	-
417005-006	DN200, DN225, DN300	Ø110	-	-	-
417111-006	DN200, DN225, DN300	Ø114.3	-	-	-

#### DISC WEDGE SADDLE



407098-001	DN200, DN225, DN300	Ø60.3	-	-	-
404712-001	DN200, DN225, DN300	Ø63	-	-	-
404713-001	DN200, DN225, DN300	Ø90	-	-	-


#### GROMMET



351628-001	DN200, DN225, DN300	Ø88.9 / Ø90	3.9 _ 4.4	-	-
351629-001	DN200, DN225, DN300	Ø88.9 / Ø90	6.4 6.9	-	-
351087-001	DN200, DN225, DN300	Ø110 / Ø114.3	4.2 4.7	-	-
351086-001	DN200, DN225, DN300	Ø110 / Ø114.3	6.5 7.0	-	-

### Industrial (Wastewater Treatment)

- Milk processing
- Leather processing
- Starch production
- Paper and pulp
- Food & Beverage
- Pharmaceutical production
- Fish Processing
- Meat Processing
- Steel manufacturing
- Electronics
- Petrochemical
- Oil Refinery
- Textile manufacturing
- Sugar
- Dairy
- Palm Oil




KID Palm Oil WWTP (Indonesia)



Namviet Fish Processing WWTP (Vietnam)



EJIP WWTP (Indonesia)



SATS WWTP (Singapore)